


# Product data sheet

TUBILUX 2250-840 PM L700 EVG  
42186460  
ZUMTOBEL



Tube Luminaire with  $\varnothing$  90 mm, Luminaire luminous flux: 2244 lm, Luminaire efficacy: 132 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Total power: 17 W, with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 80% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Suitable for ceiling mounting and horizontal or vertical wall mounting. Approved for indoor use and in unprotected outdoor areas. ambient temperature: -20°C to +35°C. Housing of impact-resistant (IK07) polymethylmethacrylate (PMMA), satin, and end caps of polyamide (PA). Age-resistant silicon seal (SI). Gear tray of double coated sheet steel, white. Flexible mounting with stainless steel fixing clips. Electrical connection via cable gland with integrated pressure equalisation element and plug connection terminal. IFS/BRC-compliant. Luminaire wired with halogen-free leads. IPX9K.. Glow-wire tested: PMMA 650°C. Dimensions: 700 x 90 x 105 mm weight: 2.3 kg.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	17 W	CRI	80
Total flux	2244 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	10%
		Total power	17 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 27.56 in  
Width: 3.54 in  
Height: 4.13 in  
Weight: 2.3 kg

## Design

Material impression: Plastic

## Electric

System power: 17 W  
Voltage: 220-240 V AC

## Protection

IK: 07