

Product data sheet

RECHTECK WAND
671229.002.1.89
RZB




IP
44

IK
03


Series: RECHTECK Luminaire for escape route identification. Housing: aluminium, with plastic corner connectors. Display panel: plastic, opal, with legend on one side. Driver integrated. Suitable for connection to central battery systems. With AC Control monitoring module for LUXIFAIR central battery units. Please indicate legend number when placing your order! Colour: traffic white, matt (RAL 9016) Length: 485 mm Width: 90 mm Height: 250 mm Weight: 2.26 kg Operating mode: maintained power mode Viewing Distance: 43 m Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 70 System power: 5.1 W Rated luminous flux: 90 lm Luminous flux, emergency: 90 lm System power, emergency: 5.1 W Control gear: Regulated power supply Protection class: I Type of protection: IP 44

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.1 W	CRI	70
Total flux	90 lm	LOR	100%
Luminous efficacy	18 lm/W	ULOR	15%
		Total power	5.1 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.1 W	CRI	70
Total flux	90 lm	LOR	100%
Luminous efficacy	18 lm/W	ULOR	15%
		Total power	5.1 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.54 in
Width: 19.09 in
Height: 9.84 in

Electric

System power: 10.2 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Design

Color of housing: White

Protection

IP: 44

IK: 03