Product data sheet


ARCSHINES18FC
ARCSHINES18FC_GREEN_15DEG+60DEG FILTER
PROLIGHTS



IP 67 IK 08

The ArcShine S18FC and ArcShine S9FC are a series of slim linear LED fixtures, designed for interior and exterior applications (IP66) such as flood lighting, wall washing and accent lighting. There are two sizes available, one with 18 LEDs (100 cm) and the other with 9 (50 cm) LED emitters, 2W each, with RGB + Warm White colour mixing. Its die-cast aluminium body with tempered glass make them perfect additions to urban structures or historical buildings. Optic: 15° lenses capable of delivering multiple angles with optional holographic filters. Optional holographic symmetric and elliptical filters available: 20°, 60°, 10°x60°, 30°x60°. The ArcShine range has an on-board power supply and DMX/RDM control. The 100 cm version is controllable in two sections. Features: IP66 design, AC 100-240V and driver on-board, DMX/RDM controllable RGB + Warm White colour mixing, with 2W LED emitters Optic: 15° lenses capable of delivering multiple angles with optional holographic filters Optional holographic symmetric and elliptical filters available: 20°, 60°, 10°x60°. 30°x60°

Light output 1



1 x LED

Nominal lamp power	20.8 W	LOR	100%
Lamp flux	723 lm	Total flux	724 lm
Luminous efficacy	37 lm/W	Total power	21.8 W
CCT	0 K		
CRI	-18		

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 29.72 in
Width: 1.97 in
Height: 1.97 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 21.8 W
Controller: DMX
Color adjustable
Appliance Class: I

Protection

IP: 67
IK: 08
Surface temperature: 65°C
Designation labels: CE