


Product data sheet

X-WALL R LED 1950 PC OPAL E IP44 24 830 / L-862MM
19.4348.2211.24
LUXIONA



Indoor luminaire. Assembly: mounted on wall. The body material is aluminum. Colour - anodised aluminum. Dimensions: 862 x 56 x 60 mm. Diffuser: PC (opalescent polycarbonate). The efficiency of the optical system is 73,66%. Beam angle: asymmetric light distribution - $I_{max}=49,5^{\circ}$. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B10 (2). Luminaire luminous flux: 1396 lm. Power of luminaire: 11,1 W. Luminaire's light efficiency: 125,8 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cos ϕ : >0,95. Circuit load capacity: 46 (B10), 74 (B16), 72 (C10), 115 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP44. Impact resistant: IK04. Protection against electric shock: I. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



3 x LED			
Nominal lamp power	3.7 W	LOR	52%
Lamp flux	632 lm	Total flux	994 lm
Luminous efficacy	171 lm/W	Total power	11.1 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 33.94 in
Width: 2.20 in
Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 11.1 W
Appliance Class: I

Protection

IP: 44
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F