


Product data sheet

EMINERE 3 RGBA 100°
78
ANOLIS



Eminere was designed by Anolis for a wide range of exterior and interior applications with a variety of lens options that can be used for flood lighting, wall grazing, wall washing and accent lighting. Equipped with Anolis’ unique 18-bit colour mixing resolution ensures extra fine colour tuning as well as smooth dimming at low level of intensity. Designed in our state of the art R&D facility by industry experts with over 10 years experience in their field, Eminere is IP67 rated and can withstand extreme conditions. Eminere is available in 1, 2, 3, and 4 foot sizes (300/600/900/1200 mm) with RGBW, RGBA or PureWhite single chips as standard and is easy to control, 1 pixel per foot. Eminere fixtures can be used for both permanent and temporary installations, including various architectural and architainment applications.

Light output 1 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	65 W	CRI	84
Total flux	2480 lm	LOR	100%
Luminous efficacy	38 lm/W	Total power	65 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 36.57 in
Width: 2.99 in
Height: 4.21 in

Adjustability

Tiltable

Electric

System power: 65 W
Color adjustable
Appliance Class: I

Protection

IP: 67
IK: 06