



Product data sheet

LINEAR ULTRA OUTPUT 1200 25 W 3000 K
4058075479937
LEDVANCE



Surface luminaire with high luminous flux. Product features: Very high luminous efficacy: up to 125 lm/W. Robust metal housing and PC diffusor. Wiring at back side of luminaire. Through wiring possible. Product benefits: Replacement of conventional T8 luminaires with up to 7100 lm. Energy savings up to 60 % (compared to luminaires that use fluorescent lamps). Robust structure with IK08. 5 years guarantee. Areas of application: Direct replacement for luminaires with fluorescent lamps. Indoor applications. Industrial and commercial halls. Public areas. Corridors, stairwells, basements. Equipment / Accessories: Mounting screws and dowels included.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	2500 W	CRI	80
Total flux	2850 lm	LOR	100%
Luminous efficacy	1 lm/W	ULOR	11%
		Total power	2500 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4,598.43 in
Width: 244.09 in
Height: 291.34 in
Weight: 1260 kg

Adjustability

Fixed

Design

Material impression: Stainless steel
Color of housing: White

Electric

System power: 2500 W
Appliance Class: I

Protection

IP: 20
IK: 08
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 14...104°F