


Product data sheet


QUADRO.QUIET GREEN SUSP. ANTHR./SW L DI/ID VDT
T6GH34X-QASWC2830H3D
PLANLICHT



IP
20


LED HO 3000K 186W 15790lm DALI CRI90 <https://katalog.planlicht.com/en-gb/fam-quadro/>

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	23.25 W	CRI	90
Total flux	1974 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	34%
		Total power	23.25 W

Mounting mode

Pendant

Shape and measurements

Length: 26.38 in

Width: 136.46 in

Height: 2.60 in

Adjustability

Fixed

Electric

System power: 186 W

Protection

IP: 20