
Product data sheet

SLOIN A SL LED4400-830 L2774 PC
42184399
ZUMTOBEL



LED light line with DALI-controllable LED converter, with cover to 50m from one piece; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 4335 lm, Luminaire efficacy: 100 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. Luminaire of aluminium, silver powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP40 below (IP20 above). Dimensions: 2774 x 76 x 98 mm weight: 11.5 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	43.3 W	CRI	80
Total flux	4335 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	43.3 W

Mounting mode

Pendant

Shape and measurements

Length: 109.21 in
Width: 2.99 in
Height: 3.86 in
Weight: 11.5 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 43.3 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 07
Designation labels: CE, ENEC