


# Product data sheet

FLAT BASIC  
211396.002.1  
RZB



IP  
43

IK  
02

Series: Flat Basic Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 230 V / 50 Hz Base: plastic. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 200, H 106 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 380lm System power: 9W Beam Angle: 135° Unified Glare Ratio: 17,9 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	380 lm	LOR	100%
Luminous efficacy	42 lm/W	ULOR	25%
		Total power	9 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 4.17 in  
Diameter: 7.87 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 9 W

## Protection

IP: 43  
IK: 02