

Product data sheet


ALFRED /1 R U LED (SYMMETRICAL)
5.705.9022.05-24LK1
LEIPZIGER LEUCHTEN



IP
65

recom. pole height: 3.00m – 5.00m light standards: low and medium lighting requirements lamp: incl. 1 glare-free U LED module colour temperature: 3.000K warm white or 4.000K neutral white LED gear: electronic driver, up to 85.000 hours, high efficiency factor of 94%, with soft start function and Constant Light Output (CLO) in order to keep the luminous flux the same over the entire life time LED life expectancy: up to 50.000 hours/ L100/ B10 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming or external change of dim settings subsequently optical system: louvre system with inner laying satined anti-glare tube and vertically mounted directed U LED module for wide spacings light distribution: symmetrical or asymmetrical luminaire head: with hinge, spike made of corrosion-resistant cast aluminium, luminaire body and canopy made of stainless steel, powder coated colour: RAL or DB glazing: PMMA RESIST, clear, clear frosted or satined; high-impact resistant wiring: completely wired; incl. cable installation: for top entry ø 76mm; delivered in one piece accessory: column, cable junction box, pole accessories – to be ordered separately application areas: parkways, boulevards, schools, hotels, factory premises, residential and local distributor roads, paths

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	70
Total flux	1249 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	28%
		Total power	13 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 38.19 in

Diameter: 18.90 in

Adjustability

Height adjustable

Electric

System power: 13 W

Protection

IP: 65