
Product data sheet

RING50
RG50Z-089402-HXXXM
EGLO




pendant mounted dir-indir LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.33 W	CRI	90
Total flux	951 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	8.33 W

Mounting mode

Pendant

Shape and measurements

Length: 34.45 in
Width: 34.45 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 66.64 W

Protection

IP: 20
Designation labels: CE