
Product data sheet


SINUS.QUIET RECESSED FRAME SILVER PRISM. 1546MM
R33E154-QASIE1840L3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


low output LED 4000K CRI 90 56,8W 7370lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,4% https://katalog.planlicht.com/en-gb/fam-sinus-quiet/

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.1 W	CRI	90
Total flux	921 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	34%
		Total power	7.1 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 60.87 in
Width: 60.87 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 56.8 W

Protection

IP: 40