

# Product data sheet

ELLK 92018/18 CG-S


12265881103

EATON EMERGENCY LIGHTING



Explosion protected luminaire for tubular fluorescent lamps, with CEWA GUARD monitoring and 20 digit address switch


## Light output 1



### 2 x Fluorescent lamp tubular T5

Nominal lamp power	18 W	Socket	G13
Lamp flux	1350 lm	LOR	76%
Luminous efficacy	57 lm/W	ULOR	9%
CCT	4000 K	Total flux	2049 lm
CRI	85	Total power	36 W

## Light output 2 (emergency)



### 1 x Fluorescent lamp tubular T5

Nominal lamp power	18 W	Socket	G13
Lamp flux	1350 lm	LOR	83%
Luminous efficacy	31 lm/W	ULOR	9%
CCT	4000 K	Total flux	1121 lm
CRI	85	Total power	36 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 29.92 in

Width: 7.28 in

Height: 5.12 in

## Adjustability

Fixed

## Electric

System power: 72 W

Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Central battery feed-in

Emergency sign: N/A

## Protection

IP: 66

IK: 03