Product data sheet


INFINITE PRO 1700MM RECESSED HALOPRISMA
AK19-19X9HPXB14
LEDSC4



IP 40

LedsC4 Infinite Pro 1700mm Recessed Haloprisma AK19-19X9HPXB14V3 Lineal lighting system for indoor use. For downlighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Haloprisma. Warranty: 5 Years. Product net weight (Kg): 4.33 Product length (mm): 1700 Product width or diameter (mm): 75 Product height (mm): 82 Ø of the hole for recessing (mm): 1705x65 Permitted ceiling thickness: 0-25 Class 1. Luminaire not suitable for coating with insulation materials. IP: IN IP20 / OUT IP40. LED. No. of lampholders or LEDs: 1. Driver brand: TCI. Maximum power of light source: 18.8W. Colour temperature: 4000K. Colour rendering index: 92. MacAdam Steps: 3. Hours of life: 80.000h L80B20. UGR: 15.4. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 2318. Real lm/W: 114. Voltage / frequency range: 220-240/50-60Hz. Voltage: 144. Equipment included: Yes. Total power: 20.3. Power factor: 0.95. Dimmable equipment included: CASAMBI.

Light output 1



1 x LED

Nominal lamp power	20.3 W	LOR	100%
Lamp flux	2318 lm	Total flux	2318 lm
Luminous efficacy	114 lm/W	Total power	20.3 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 66.93 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 20.3 W
Appliance Class: I

Protection

IP: 40