


# Product data sheet

MERCMaster LED EMERGENCY 4K LUMEN NEMA TYPE V 4000 K CCT  
I/MLLEDA33ND5BUH  
APPLETON (EMERSON EGS)




Mercmaster LED Low Profile Series EMERGENCY 3/4" NPT Hub Diffused Polycarbonate globe NEMA Type V Symmetrical 4000 K CCT/ 80 CRI  
Voltage- BU-120-277V, 50/60Hz, 125-300 Vdc BH-347-480 Vac, 50/60Hz Class I, Division 2, Groups A, B, C, D Class I, Zone 2, AEx ec IIC Zone 21, AEx tb IIIC Class I, Zone 2, Ex ec IIC Class II, Division 1, Group E, F, G Zone 20, Group IIIC Class II, Division 2, Group F, G Class III  
Simultaneous Exposure Type 3R, 4X IP66 Suitable for Use in Wet Locations Marine Outside Type (Salt Water) DLC Qualified Product listed  
Refer to catalog for additional options

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	5181 K
Nominal lamp power	12.9 W	CRI	70
Total flux	3153 lm	LOR	100%
Luminous efficacy	244 lm/W	Total power	12.9 W

## Light output 2 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	37.4 W	CRI	80
Total flux	3989 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	37.4 W

## Mounting mode

Pendant

## Shape and measurements

Height: 1.00 in

Diameter: 7.50 in

## Adjustability

Fixed

## Electric

System power: 50.3 W

Appliance Class: II

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 67

Explosion zone suitability: 2, 20, 21