
Product data sheet

PRISMA 2X28W OP
96004826
THORN LIGHTING



Slim surface mounted IP44 fluorescent luminaire for 2 x 28W T16 lamp(s) with electronic - fixed output gear. Body in white painted galvanized steel sheet with white plastic end caps and a opal acrylic diffuser. Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or brackets. Fixing centres: 1100mm. Two cable entries Ø19mm in the centre of the body. Grommets included. Piano key terminals 5 x 2 x 2.5mm². Can be suspended using wire suspension accessory kit (to be ordered separately). Lamp to be ordered separately. Dimensions: 1216 x 166 x 64 mm Total power: 61 W Weight: 2.3 kg Luminaire efficacy: 62 lm/W

Light output 1



2 x General service incandescent lamp

Nominal lamp power	28 W	LOR	72%
Lamp flux	5200 lm	ULOR	6%
Luminous efficacy	123 lm/W	Total flux	7533 lm
CCT	3000 K	Total power	61 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 47.87 in
Width: 6.54 in
Height: 2.52 in
Weight: 2.3 kg

Design

Material impression: Plastic
Color of housing: White

Electric

System power: 61 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 44
Designation labels: CE