Product data sheet


FORREY 7 BOLLARD
FOR-10121-T3-W40
LIGMAN



IP 65 IK 08

- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Opal, impact-resistant, UV-stabilised polycarbonate diffuser - Models with shade will have colour white coating at inside of shade luminaire and outside surface coating according to colour of luminaire - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	70 W	CRI	80
Total flux	7532 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	100%
		Total power	70 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 32.44 in
Diameter: 12.60 in
Weight: 6.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 70 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C