# Product data sheet

LIGHTALK 8 WALL WASHER FLOODLIGHTS LA-30021-W-W40


LIGMAN



IP 67 II (±

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° C 135,000, 300,000 - Life time L80B10 Ta 50° C 310,000, > 500,000 - Die-cast aluminium end-caps, extruded aluminium housing and aluminium front frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear for LA-30001, LA-30002, LA-30013, LA-30014 - Remote driver is included for LA-30021, LA-30022

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	28.6 W	CRI	80
Total flux	2310 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	100%
		Total power	28.6 W

## Mounting mode

Wall mounted, Floor mounted

#### Shape and measurements

Length: 3.54 in Width: 23.86 in Height: 2.56 in Weight: 2.1 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 28.6 W Voltage: 230 V AC Ballast: ECG Controller: Dimmable 1..10V, DALI Appliance Class: I

## Protection

IP: 67 IK: 10 Surface temperature: 40°C