

Product data sheet

CUBIC SURFACE - Y2
CY2AEE-830M-Q330
LIGHTNET



LED surface-mounted luminaire for walls or ceilings. Direct only light distribution. Luminaire body made of aluminum profile. Surface natural anodised or white, graphite, black or champagne coated as well as polished aluminium. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2700K, 3000K, 3500K, 4000K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Sophisticated mounting system for easy installation and stable hold. On request: Integration of emergency lighting components, sensor technology.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	82
Total flux	1272 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 12.99 in
Width: 12.99 in
Height: 2.17 in

Adjustability

Fixed

Electric

System power: 12 W

Protection