

# Product data sheet

FLAT POLYMERO KREIS  
311611.002.4  
RZB




IP  
40

IK  
10

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, H 93 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 2100lm System power: 29W Beam Angle: 119° Number of fittings B10A: 5 Number of fittings B16A: 13 Number of fittings C10A: 14 Number of fittings C16A: 22 Inrush current: 20A Unified Glare Ratio: 18,5 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	29 W	CRI	80
Total flux	2100 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	10%
		Total power	29 W

## Mounting mode

Ceiling mounted

## Electric

System power: 29 W

## Shape and measurements

Height: 3.66 in  
Diameter: 18.11 in

## Protection

IP: 40  
IK: 10

## Adjustability

Fixed