
# Product data sheet

MEDICAL AND CLEANROOM LIGHTING

V1-C0-0R080-01HGA-5403540 C070 595*595*95 MM IP54 WITH HOMOGENOUS ILLUMINATION 35W 4000K OPAL EM 1H


VARTON



IP 54 IK 08

Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ2 Protection class: I Mounting method: Surface mounting/recessed mounting Ingress protection (IP): IP54 Radiation angle: 120 Impact resistance: IK08 Power factor: 0,95 https://www.varton.ru/products/svetilniki-dlya-chistykh-pomeshcheniy/c-seriya-ip54-s-ravnomernoy-zasvetkoy/c070-u-595-595-95-mm-ip54-universalnye-s-ravnomernoy-zasvetkoy/svetodiodnyy-svetilnik-varton-c070-u-meditsinskiy-35-vt-cri90-4000-k-vstraivaemyy-nakladnoy-595kh595_19/

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 35 W | LOR | 100% |
| Lamp flux | 3850 lm | Total flux | 3850 lm |
| Luminous efficacy | 110 lm/W | Total power | 35 W |
| CCT | 4000 K | | |
| CRI | 90 | | |

### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 3.74 in

### Adjustability

Fixed

### Electric

System power: 35 W

### Protection

IP: 54
IK: 08