



# Product data sheet

QUADRANA  
311728.004  
RZB



Series: Quadrana Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Decorative wall and ceiling luminaire made of pressure die-cast aluminium. Opal PMMA diffuser. Tool-free access with two ellbow lever locks. Integral LED module for direct mains voltage connection. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 300, B 300, H 115 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 300lm System power: 5W Beam Angle: 106° Unified Glare Ratio: 13,0 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	60 lm/W	ULOR	22%
		Total power	5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 11.81 in

Width: 11.81 in

Height: 4.53 in

## Adjustability

Fixed

## Electric

System power: 5 W

## Protection

IP: 40

IK: 05