


Product data sheet

RUBIN CLEAN LED 2600 PLX E IP65 34 840 / 610X310MM


19.4063.2121.34

LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9016 (white). Luminaire dimensions: 610 x 310 x 78 mm. Weight 3,55 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 75,03%. Beam angle: (C0-C180) / (C90-C270) - 105° / 104,8°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 1964 lm. Power of luminaire: 14,4 W. Luminaire's light efficiency: 136,4 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 46 (B10), 74 (B16), 72 (C10), 115 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP65. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



2 x LED			
Nominal lamp power	7.2 W	LOR	83%
Lamp flux	1308 lm	Total flux	2183 lm
Luminous efficacy	182 lm/W	Total power	14.4 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.02 in

Width: 12.20 in

Height: 3.07 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 14.4 W

Appliance Class: I

Protection

IP: 65

IK: 04

Other operating numbers

Ambient temperature range: 41...86°F