Product data sheet

NEOPLACE DIRECT
7760-I-3-677-XX
UNILAMP



IP 66 IK 10

EPSYLON is the family of pole top and wall mount luminaires with unshielded symmetrical distribution. The recommended mounting height is between 3 – 5 meters. To avoid discolouration of the lens we have used a high quality PMMA clear cover. The diffuser gives a broad spread light distribution. These luminaires are generally used to illuminate gardens, parks, pedestrian, squares and open spaces. They are assembled with high brightness multiple LEDs. Aluminium pole, galvanized steel pole, pole adaptor and anchorage unit for concrete foundation are also available. • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Spun Aaluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Clear PMMA diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • M20 cable gland or TPE grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED

Nominal lamp power	24 W	LOR	88%
Lamp flux	3040 lm	Total flux	2670 lm
Luminous efficacy	127 lm/W	Total power	25 W
CCT	2700 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 11.79 in

Adjustability

Fixed

Electric

System power: 25 W
Appliance Class: I

Protection

IP: 66
IK: 10