Product data sheet

LUPALO STELE
612235.0131
RZB



IP 00

Series: LUPALO Luminaire tube with anchoring tube. Height 4150 mm. Post tube of the modular LUPALO column system. Standpipe made of corrosion-resistant aluminium profile, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Inspection door with triangular lock. C-rail for junction box/cable junction box. Connection box on base, max. 2 x 3 x 2.5 mm² for through wiring. Continuous buried base with two side cable holes. Please order fuse box separately. Modular design: Please order light top unit separately. Colour: anthracite metallic (DB703) Diameter: 180 mm Height: 4150 mm Tube diameter Dro: 180 mm Pole-top diameter Dzo: 180 mm Recess height: 1000 mm Weight: 40 kg

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	0.01 W	CRI	80
Total flux	1 lm	LOR	28%
Luminous efficacy	100 lm/W	ULOR	8%
		Total power	0.01 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Height: 163.39 in
Diameter: 7.09 in

Adjustability

Fixed

Electric

System power: 0.01 W

Protection

IP: 00