

Product data sheet


LUGTRACK 5 LED 3000 6400LM 3000K OPAL PLEXIGLASS (PLX) WHITE
080091.5L21.21

LUG



Modern LED luminaire for quick assembly, construction of the luminaire enables quick, easy and tool-less connection into long lighting systems (available in 1,5m and 3m-long dimension) by the usage of mounting elements. Mounting: suspended, on wire suspension (on request) Body: powder-painted steel sheet, aluminium Power: 220-240V 50/60Hz Lifetime (L70B50): 50 000 h Operating temperature range: 0°C ... +45°C Additional information: The possibility of using one or more power supplies in the luminaire. Additional equipment: accessories Other remarks: in order to supply a particular lighting system , the supply connector shall be ordered Warranty: 5 years Application: supermarkets, delicatessen, warehouses, industrial facilities

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	52 W	CRI	80
Total flux	3200 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	52 W

Mounting mode

Pendant

Shape and measurements

Length: 118.11 in

Width: 4.37 in

Height: 3.54 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 52 W

Appliance Class: I

Protection

IP: 20

IK: 05