

Product data sheet

1W 3000K 12° HS

L51


MP LIGHTING



IP
40

12° Half Shroud Application Showcases, kitchen cabinets, restaurant millwork, or wine cellars. Recommended Projects - Commercial, Institutional, Retail, Clinic, Hospitality, Religious, Educational, Architecture IP Rating 40 Mounting Surface mount to cabinet millwork. Comes with 2'(610mm) wire lead. Optimal spacing is 18" - 24"(457mm - 610mm). Electrical Power by remote constant current driver. *See website for recommended drivers *Remote emergency driver / inverter options available (consult factory). Power Consumption 1.5 Watt (at 350mA, 1 Watt) 3.0 Watt (at 700mA, 2.5 Watt) Light Output 1 Watt, 46-78lm 2.5 Watt, 65-154lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Solid anodized aluminum, RoHS compliant.

Light output 1



1 x LED

Nominal lamp power	1 W	LOR	80%
Lamp flux	68 lm	Total flux	54 lm
Luminous efficacy	54 lm/W	Total power	1 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.50 in

Width: 1.50 in

Height: 1.33 in

Adjustability

Fixed

Electric

System power: 1 W

Protection

IP: 40