


Product data sheet

APOLLO G2 1560MM PM 1X62W 030° 10200LM
9401555D
PRACHT



Food-certified Reflector luminaire APOLLO G2 1560mm PM 1x62W 030° 10200lm 4.000K, class II, without TW. New generation of the APOLLO damp-proof reflector luminaire. Swiveling reflectors. Acid and alkali resistant. IP65 protection class. Ideal for industry and logistics. 5-year warranty. Item number: 9401555d GTIN: 4018098470250 Technical details/specification: Cover made of PM; Housing made of GRP polyester White RAL 9010; 220–240 V 0/50/60 Hz; Energy efficiency class B; Number of light sources / LED rows: 1; IP65; Through-wiring in mm²: Without; Dimensions: LxWxH: 1560mm x 105mm x 152mm; Diameter: mm

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	62 W	CRI	80
Total flux	10200 lm	LOR	100%
Luminous efficacy	165 lm/W	Total power	62 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.42 in
Width: 4.13 in
Height: 5.98 in
Weight: 3.1 kg

Adjustability

Tiltable

Design

Color of housing: White

Electric

System power: 62 W
Appliance Class: II

Protection

IP: 65
IK: 06

Other operating numbers

Ambient temperature range: -4...104°F