Product data sheet


7800 FOCO XL LED FLOODLIGHT
7800 12803A 730 LMS IR (78000 0109)
SCHUCH



IP 66 IK 09

LED floodlight, FOCO XL, 281 W, 37130 lm, 132 lm/W, Class I, IP66, asymmetrical beam, 3000 K, CRI≥ 70, Ta -40 °C/+40 °C, L90>100000 h (@ Ta max), LIMAS, IR-sensor, Pane Safety glass clear, Housing Die-cast aluminium, Colour grey, DB702N. LED floodlight FOCO XL of the GreenLine series with outstanding sustainable product design. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with LED modules, lower part with ECG, tempered safety glass pane, cable entry and strain relief, hinged. Zhaga LED modules, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Mounting bracket with swivel range of 180°. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 648,00 mm, Width/Diameter 540,00 mm, Height 100,00 mm, Net weight 17,00 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	281 W	CRI	70
Total flux	37129 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	7%
		Total power	281 W

Mounting mode

Pole top mounted, Wall mounted

Shape and measurements

Length: 25.51 in
Width: 21.26 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 281 W
Appliance Class: I

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 66
IK: 09
Designation labels: CE