Product data sheet

ILDL421SC-SW-TT - SPOT
ILDL421SC-SW-TT
RP-TECHNIK

IP 40 IK 03

The LED safety luminaire IL with its unobtrusive design is a real all-rounder. it is equipped for virtually all requirements and always provides the right solution. Since the status LED is fitted in the lens, the harmony of the discreet housing is not interrupted. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types depending on the specific application. A round lens and hall lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. The IL surface-mounted luminaire comprises just 2 parts; the ceiling section contains the mains supply terminals. The actual luminaire is mounted without the need for tools and is free of mains voltage upon disassembly.

Light output 1 (emergency)



1 x LED

Nominal lamp power	1.9 W	LOR	89%
Lamp flux	250 lm	Total flux	223 lm
Luminous efficacy	132 lm/W	Total power	3 W
CCT	6500 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 1.42 in
Diameter: 3.94 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 3 W
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 40
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: 5...104°F