
# Product data sheet

X-LINE SLIGHT LOW UGR L-DOWN LED 3000 LOUVER E 24 830 LINE-S / L-1196MM S-1,5M
19.4420.2411.24


LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - anodised aluminum. Dimensions: 1196 x 34 x 68 mm. Diffuser: LOUVER (anti-glare louver). The efficiency of the optical system is 71,66%. Beam angle: (C0-C180) / (C90-C270) - 46° / 44,6°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 145000 h L90/B10. Luminaire luminous flux: 2066 lm. Power of luminaire: 19,1 W. Luminaire's light efficiency: 108,2 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 74 (B10), 72 (B20), 115 (C10). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

## Light output 1



3 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 6.267 W | LOR | 52% |
| Lamp flux | 961 lm | Total flux | 1512 lm |
| Luminous efficacy | 153 lm/W | Total power | 18.8 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

### Mounting mode

Pendant

### Shape and measurements

Length: 47.09 in
Width: 1.34 in
Height: 2.68 in

### Adjustability

Fixed

### Design

Color of housing: Silver gray

### Electric

System power: 18.8 W
Appliance Class: I

### Protection

IP: 40
IK: 04

### Other operating numbers

Ambient temperature range: 41...95°F