



Product data sheet

EASY KAP 105
03.4455.BU/QR-CBC/50W/10°24°36°60°
FLOS




Luminaire for recessed mounting on ceilings for halogen, metal halide and LED lamps. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1182 lm	LOR	56%
Luminous efficacy	13 lm/W	Total flux	662 lm
CCT	3000 K	Total power	50 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	856 lm	LOR	55%
Luminous efficacy	9 lm/W	Total flux	471 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	857 lm	LOR	53%
Luminous efficacy	9 lm/W	Total flux	453 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1054 lm	LOR	57%
Luminous efficacy	12 lm/W	Total flux	600 lm
CCT	3000 K	Total power	50 W
CRI	99		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.38 in

Diameter: 4.13 in

Adjustability

Fixed

Electric

System power: 50 W

Protection

IP: 20