Product data sheet


INFINITE PRO 1136MM SURFACE OPTICELL
AK14-32X9CLOU14
LEDSC4



IP 40

LedsC4 Infinite Pro 1136mm Surface Opticell AK14-32X9CLOU14 Lineal lighting system for indoor use. For downlighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opticell. Warranty: 5 Years. Product net weight (Kg): 2.36 Product length (mm): 1136 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP40. LED. No. of lampholders or LEDs: 1. LED brand: TRIDONIC. Driver brand: TCI. Maximum power of light source: 29.3W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 17.4. Photobiological risk: RG1. % de Flickering: <3%. Real flux (lm): 4319. Real lm/W: 132. Voltage / frequency range: 99-305/50-60Hz. Voltage: 160. Equipment included: Yes. Total power: 32.6. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	32.62 W	LOR	100%
Lamp flux	4319 lm	Total flux	4318 lm
Luminous efficacy	132 lm/W	Total power	32.62 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 44.72 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 32.62 W
Appliance Class: I

Protection

IP: 40