


Product data sheet

SPIKE GRAPHITE UPLIGHT 930LM 3000K RA>80 TRAILING EDGE DIMMING
7021986239133
SG ARMATUREN



Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct/Indirect Light technic LED 16W (10W+6W) 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP44 IK08 Materials and finish Housing: Aluminium Colour: Graphite Optics: UV-stabilized polycarbonate/ UV-stabilized PMMA Mounting/Connection Surface, Outdoor Screwless terminal block

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	930 lm	ULOR	6%
Luminous efficacy	58 lm/W	Total flux	930 lm
CCT	3000 K	Total power	16 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 6.53 in
Width: 6.01 in
Height: 6.69 in

Adjustability

Fixed

Electric

System power: 16 W
Appliance Class: I

Protection

IP: 44
IK: 08