


# Product data sheet

ODESSA 1 FLOODLIGHTS,PROJECTORS  
OD-50002-VN-W40-A80214  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° > 60,500 - Life time L80B10 Ta 50° > 60,500 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request for OD-50011, OD-50012 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Arm mounting installation - Integral control gear

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4032 K |
| Nominal lamp power | 11.2 W  | CRI         | 80     |
| Total flux         | 722 lm  | LOR         | 100%   |
| Luminous efficacy  | 64 lm/W | Total power | 11.2 W |

## Mounting mode

Standing / Bollard, Wall mounted

## Shape and measurements

Height: 7.28 in  
Diameter: 4.13 in  
Weight: 1.7 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 11.2 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 66  
IK: 07  
Surface temperature: 40°C