


Product data sheet

URBINO TWILIGHT LED 102W 12650LM 3000K IP66 O8 - FOR TOWN AND LOCAL ROADS GRAY I
130222.5L461.081.986
LUG



Professional streetlight luminaire for LED light sources. Luminaire with twilight sensor. High efficacy to 131 lm/W Mounting: on pillar $\varnothing 60/76\text{mm}$, on outriggers $\varnothing 60/76\text{mm}$ Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.054 m^2 Power supply efficiency $>95\%$ Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, knife switch, 10kV surge protection, NTC, access to the driver chamber without the use of tools. Additional information: tilt adjustment: -15° to $+15^\circ$ (every 5°). Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenade, cycle paths. Type of optics: O8 - for town and local roads

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	102 W	CRI	70
Total flux	12650 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	102 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in

Width: 9.84 in

Height: 7.68 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 102 W

Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor

Protection

IP: 66

IK: 08