


Product data sheet

WLF-IP44 II FLEX 3000K 20W DIM OPAL
7216801
WESTAL



Industrial luminaire made of steel with a cup in microprismatic polycarbonate with removable opal film. Armed with an adjustable LED unit with adjustable color temperature 3000K/4000K and adjustable power in 4 different modes. 60cm = 11/13/16/20W, 120cm = 23/29/35/40W 150cm = 26/33/40/47W. Montage poem ceiling. WLF IP44 II 600mm comes with terminal block 5x2.5mm² in the middle of the luminaire. WLF IP44 II 1200mm and 1500mm come with 3 terminal blocks. 1st in the middle and one at each end of the luminaire. Easy to open, install and maintain. Suitable in several environments such as kitchens, corridors, etc.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	80
Total flux	2736 lm	LOR	100%
Luminous efficacy	137 lm/W	ULOR	2%
		Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.43 in
Width: 6.18 in
Height: 2.28 in

Adjustability

Fixed

Electric

System power: 20 W
Appliance Class: I

Protection

IP: 44
IK: 10

Other operating numbers

Ambient temperature range: -13...122°F