Product data sheet


LINEDO_2,3M_AD_1111
9523AD.830.500.004
RZB



IP 54 IK 03


LINEDO, 137 W, 18400 lm, 830, aluminium, on/off Continuous line luminaire, L 2291 B 58 H 76

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	4600 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	34.25 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	4600 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	34.25 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	4600 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	34.25 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34.25 W	CRI	80
Total flux	4600 lm	LOR	100%
Luminous efficacy	134 lm/W	Total power	34.25 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 90.20 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 137 W

Protection

IP: 54
IK: 03