


Product data sheet

APOLLO REMADE 1560MM PO 1X44W 060° 7200LM
9405045N
PRACHT



New sustainable generation of the proven APOLLO moisture-proof reflector luminaire. Beautifully shaped lampholder end pieces made of recycled material, newly designed. Simple one-man installation of the reflector thanks to integrated plug-in device with direction indicators and captive, easy-to-close clips made of stainless steel. Enclosed housing on all sides made of white recyclate, protection class IP65. Reflector made of PRACHTOPAL recyclate can be swivelled through 120°, with practical locking mechanism in 10° steps. Short, age-resistant silicone seals. Integrated electronic converter. Particularly robust due to thermal decoupling of LED and converter. Through-wiring up to max. 5x2.5mm² + 2x1.5mm² possible. The permissible ambient temperature is reduced by 1°C for every 2A load on the through-wiring. Variable mounting distances thanks to PRACHT CLAMP SYSTEM made of stainless steel, suitable for ceiling and horizontal wall mounting, pendant and mounting rail mounting possible with accessories.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	44 W	CRI	80
Total flux	7200 lm	LOR	100%
Luminous efficacy	164 lm/W	ULOR	2%
		Total power	44 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.42 in
Width: 4.13 in
Height: 5.98 in
Weight: 3.1 kg

Adjustability

Tiltable

Electric

System power: 44 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -13...113°F