


# Product data sheet

ROUNDED SUPERFLACH  
581603.002  
RZB




IP  
66

IK  
02

Series: Rounded Superflach Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 50 Hz Pressure die-cast housing of corrosion resistant Aluminium, powder coated, spherical cap diffuser of mouth blown opal glas with fixing clamps, drill hole deviations can be compensated, second cable entry for loop-through. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 268, H 91 Lamp: LED Life time: 45000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 410lm System power: 8,5W Beam Angle: 117° Unified Glare Ratio: 19,6 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.5 W	CRI	80
Total flux	410 lm	LOR	100%
Luminous efficacy	48 lm/W	ULOR	3%
		Total power	8.5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.94 in  
Diameter: 10.55 in

## Adjustability

Fixed

## Electric

System power: 8.5 W

## Protection

IP: 66  
IK: 02