


Product data sheet

BASIC AMBIENT SUSPENDED - G6
BG6FSE-830M-D400-U
LIGHTNET



LED pendant luminaire. Omnidirectional light distribution. Luminaire body made of aluminium profile and diffuser with overall height of 60mm. Ambient diffuser made of frosted acrylic glass for general lighting. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable central cord suspension with transparent power supply cable. On request: Integration of emergency lighting components, sensor technology.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	82
Total flux	1711 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	3%
		Total power	13 W

Mounting mode

Pendant

Electric

System power: 13 W

Shape and measurements

Height: 15.75 in
Diameter: 15.75 in

Protection

Adjustability

Height adjustable