

Product data sheet

HOLBEIN-L2WG4-CODE8-4000K-2750LM-24W
LIGHTRONICS




IP
65

IK
10

HOLBEIN STRIKING DESIGN, SPECIAL LIGHTING TECHNOLOGY It is not only the striking design that makes the HOLBEIN luminaire so distinctive; it also incorporates unusual lighting technology. The light source is positioned higher than in most luminaires. This design feature minimises light nuisance for traffic and general light pollution. Furthermore, this has been achieved without making concessions in the area of light output, impact resistance and good weather sealing. As a result, this luminaire is suitable for cycle paths, car parks, public squares and residential areas. This streetlight is waterproof (IP65) and impact-resistant (IK10).

Light output 1



1 x L2WG4-FFDA-Code8-410mA

Nominal lamp power	24 W	LOR	87%
Lamp flux	2750 lm	Total flux	2385 lm
Luminous efficacy	115 lm/W	Total power	24 W
CCT	3000 K		
CRI	99		

Mounting mode

Pole top mounted

Electric

System power: 24 W

Shape and measurements

Height: 3.94 in

Diameter: 25.98 in

Protection

IP: 65

IK: 10

Adjustability

Fixed

Design

Material impression: Plastic

Color of housing: Silver gray