




Product data sheet

VARIOPLAST I
672182.002
RZB



Item Number: 672182.002 Series: Varioplast I Type of Protection: IP 55 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Mounting support body plastic (polycarbonate), cover plastic, opal (polycarbonate), for optimum escape route illumination. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 320, B 186, H 80mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: standard Safety Marks: Ball impact proof in accordance with DIN 18032-03, D-mark, F-mark Impact Protection: IK08 (5 Joule) Luminaire flux LED: 740lm System power: 7,4W Beam Angle: 120°/110° Number of fittings B10A: 27 Number of fittings B16A: 17 Number of fittings C10A: 45 Number of fittings C16A: 28 Inrush current: 27A Unified Glare Ratio: 21,0 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.4 W	CRI	80
Total flux	740 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	7%
		Total power	7.4 W

Mounting mode

Wall mounted

Shape and measurements

Length: 7.32 in
Width: 12.60 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 7.4 W

Protection

IP: 00
IK: 08