Product data sheet

LSPO_551_LED_19W_IP54_NEUTRAL_L647MM
5878433
PETRIDIS



Recessed luminaires in staves pitch width 100, 150, 200, 300mm, or plasterboard ceiling. Technical Features - Steel body, electrostatically painted in white color. - High efficient opal PMMA for PSPO Led, microprismatic and aluminium louvre with high efficient satin PMMA cover for louvre version. - Last generation high efficient LED CHIP. - Pure light without IR/UV radiation. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - UGR<19 at specific editions: Glare Evaluation: X=4H/ Y=8H S=0,25H, reflection factors 70/50/20. For DSE work stations: γ≥ 65o <3000cd/m2. - Connection for operation on 230V/50-60Hz. Upon request: - Connection for emergency lighting system, for one or three hours.

Light output 1



1 x LED

Nominal lamp power	19 W	LOR	63%
Lamp flux	2930 lm	Total flux	1835 lm
Luminous efficacy	154 lm/W	Total power	19 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 25.47 in
Width: 7.72 in
Height: 3.74 in

Adjustability

Fixed

Design

Material impression: Chrome, Plastic

Electric

System power: 19 W
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 54
Designation labels: CE