


Product data sheet

PLANOX TUBE
601067.002
RZB




IP
67

IK
10

Series: Planox Tube Type of Protection: IP 67 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz End caps: grey plastic (polyamide). Diffuser: shock resistant opal plastic (polycarbonate). One cable inlet. Integrated converter. LED included. Available Colours: white Type of Installation: universal mounting system Dimensions: D 78, L 965, Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: D-mark, F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 3900lm System power: 33W Beam Angle: 134°/102° Number of fittings B10A: 22 Number of fittings B16A: 37 Number of fittings C10A: 38 Number of fittings C16A: 62 Inrush current: 23A Unified Glare Ratio: 26,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	33 W	CRI	80
Total flux	3900 lm	LOR	100%
Luminous efficacy	118 lm/W	ULOR	11%
		Total power	33 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.07 in
Width: 37.99 in
Height: 2.95 in

Adjustability

Fixed

Electric

System power: 33 W

Protection

IP: 67
IK: 10