


Product data sheet

URBINO LED 68W 10200LM 4000K IP66 O38 - FOR AREA LIGHTING GRAY I
130222.5L771.181
LUG



Professional streetlight luminaire for LED light sources. High efficacy to 156 lm/W Mounting: on pillar $\varnothing 60/48\text{mm}$, on pillar $\varnothing 76\text{mm}$ - modification .829, on outriggers $\varnothing 60/48\text{mm}$, on outriggers $\varnothing 76\text{mm}$ - modification .829. Body: high pressure die-cast aluminum. Lateral Surface Wind Exposed: 0.039 m^2 . Power supply efficiency >95% Power: 220-240V 50/60Hz. Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, twilight sensor, knife switch, 10kV surge protection, NTC. Additional information: Tilt adjustment: -15° to $+15^\circ$ (every 5°). Additional equipment: additional anti-corrosive protection (index extension: .985), access to the driver chamber without the use of tools (index extension: .825), luminaire with holder for mounting on a $\varnothing 76\text{mm}$ pillar (index extension: .829). Other remarks: the pole and boom are not part of the luminaire. Warranty: 5 years. Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenades, cycle paths. Type of optics: O38 - for area lighting

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 68 W | CRI | 70 |
| Total flux | 10200 lm | LOR | 100% |
| Luminous efficacy | 150 lm/W | Total power | 68 W |

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in
Width: 9.84 in
Height: 3.94 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 68 W
Appliance Class: I

Protection

IP: 66
IK: 09