

# Product data sheet

TANTO 1100 WHITE 440LM 3000K RA>80 TWILIGHT


7021986415445

SG ARMATUREN



Design: Hallvard Jakobsen Attractive, round wall luminaire with half-diffuser and cross that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Several variants with integrated sensor or dimming relay. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 8W 3000K Ra>80 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Twilight Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

## Light output 1



### 1 x LED

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 8 W     | LOR         | 100%   |
| Lamp flux          | 440 lm  | Total flux  | 440 lm |
| Luminous efficacy  | 55 lm/W | Total power | 8 W    |
| CCT                | 3000 K  |             |        |
| CRI                | 80      |             |        |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 10.63 in

Width: 4.84 in

Height: 10.63 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 8 W

Appliance Class: II

## Protection

IP: 65

IK: 10