Product data sheet


DAMP-PROOF DIFFUSER LUMINAIRE SPLASH 36- 42W 4650- 5800LM C
2008.9164 - SPLASH 1572 LED4650-5800-840 NB PMMA ONF E3H ML
REGENT



IP 66 IK 06

Damp-proof diffuser luminaire Splash for surface, wall, pendant mounting and mounting rail, with LED, system power: 36 - system power: 42 W, luminous flux of luminaire 4650 - luminous flux of luminaire 5800 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 63'000 h, L80 130'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 5.5 A, direct light emission, concentrated beam, 1 integral control gear, ON/OFF, with emergency unit, for non-maintained and maintained mode, with self-test, complete with battery pack, (burning life 3h), housing in acrylonitrile butadiene styrene (ABS), dark grey and diffusor in polymethyl methacrylate (PMMA), transparent, with chrome steel clamps, System power and choice of 3 luminous flux levels, can be set directly on the luminaire 36-40-44 W / 4650-5300-5800 lm protection class I, ingress protection IP66, glow wire test 650 °C, impact strength: IK 06, for ambient temperatures 0 to +50 °C, this product contains a light source of energy efficiency class A and EPREL registration number: 1459375 L = 1572 mm, B = 95 mm, H = 100 mm

Light output 1



1 x LED

Nominal lamp power	49 W	LOR	100%
Lamp flux	5800 lm	ULOR	8%
Luminous efficacy	118 lm/W	Total flux	5802 lm
CCT	4000 K	Total power	42 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.89 in
Width: 3.74 in
Height: 4.37 in

Adjustability

Fixed

Electric

System power: 42 W
Appliance Class: I

Protection

IP: 66
IK: 06