Product data sheet


LINA45-S 145S-5B1Z-35GGM3/840, B
145S-5B1Z-35GGM3/840
HALLA



IP 20


145S-5B1Z-35GGM3/840, B Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1964 x 47 x 69 mm Type of installation: Suspended Distribution: Direct-indirect wide-lighting distribution Optics type: Plastic louvre low UGR Protection class: I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	260 lm	LOR	100%
Luminous efficacy	173 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	50.9 W	CRI	80
Total flux	7700 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	50.9 W

Mounting mode

Pendant

Shape and measurements

Length: 1.85 in
Width: 77.32 in
Height: 2.72 in

Adjustability

Fixed

Electric

System power: 52.4 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20