


# Product data sheet

MINISILVIA  
934021  
FLOS



• Outdoor luminaire for installation on wall, ceiling and floor. The version “on post” is only for installation on floor. • Configuration: die-cast aluminium structure EN AB-47100 alloy (low copper content), extruded aluminium pole (version “on post”), borosilicate transparent or sandblasted glass, moulded silicone gaskets. Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	10 W	Socket	G24Q-1
Lamp flux	600 lm	LOR	9%
Luminous efficacy	5 lm/W	ULOR	2%
CCT	2700 K	Total flux	53 lm
CRI	82	Total power	10 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 7.48 in  
Diameter: 5.12 in

## Adjustability

Fixed

## Electric

System power: 10 W  
Appliance Class: I

## Protection

IP: 65  
IK: 07